



DBA Series

Aluminum Frame Cold Water Pressure Washers

#1 in North America for High-Pressure Cleaning Equipment

Gasoline / Direct Drive



Weldless corrosion resistant **aluminum frame** with 1-1/4" handles for maximum durability

Easy to push and pull thanks to an innovative frame shape and ideal weight distribution

Handle also adjusts for height for **ergonomical operation**

Four quick-couple nozzles made of hardened stainless steel and color-coded for easy spray pattern selection: 0°, 15°, 25° & 40°

Reliable **Honda GX** commercial-duty gasoline engines with 3-year warranty and vibration isolation for smooth operation

Pump support bracket extends engine crankshaft service life

The commercial-duty **Crankcase pump** carries a 7-year limited warranty... best in the industry!

Thermal pump protector prevents excessive heat or pressure buildup for safety

Cast aluminum rotary joints allow **the handle to fold down** for storage and easy transport.

Hose and gun hangers keeps spray wand and hose safely stored

Professional-duty **Trigger gun and spray wand** with adjustable side grip

50 ft. steel-wire braided high-pressure hose includes 24-inch hose guard for burst protection and swivel crimp fitting for tangle-free handling. Rated for 4,000 PSI.

FEATURES

- 2.5 to 3.8 GPM / 2700 to 4000 PSI
- 196 to 389 CC Gasoline Engines
- Aluminum frames, lightweight design
- 7-yr pump warranty

10" 4-ply tubed pneumatic tires for easy maneuvering

Two Rubber Pad Feet absorb vibration and keep machine from "walking"

www.Hotsy.com

Nothing Cleans Like a Hotsy!

DBA SERIES Cold Water GASOLINE Models

■ 196 to 390 CC gasoline engines ■ 2.5 to 3.8 GPM @ 2700 to 4000 PSI ■ Compact / lightweight design ■ 7-yr Hotsy pump warranty

The Hotsy DBA Series: The Right Choice for Tough, Cold-Water Cleaning

SPECIFICATIONS

MODEL	GPM	PSI	CC's (HP)	ENGINE	START	PUMP MODEL	DRIVE	HOSE	DIMENSIONS	SHIP WT (lbs)
DBA-252739	2.5	2700	196 (6.5)	Honda GX200	RECOIL	HG2530G.1	DIRECT	50'	39.3"Lx22.5"Wx39.6"H	125
DBA-303039	3.0	3000	270 (9)	Honda GX270	RECOIL	HG3035G.1.1	DIRECT	50'	39.3"Lx22.5"Wx39.6"H	148
DBA-354039	3.5	4000	390 (13)	Honda GX390	RECOIL	HS3540G.3	DIRECT	50'	41"Lx23"Wx40"H	167
DBA-383539	3.8	3500	390 (13)	Honda GX390	RECOIL	HS4040G.2	DIRECT	50'	40.8"Lx22.5"Wx39.6"H	172

DON'T FORGET THE SOAP!

Hotsy pressure washers clean best when matched with specially formulated Hotsy detergents. Nearly all contain Hotsy's exclusive advanced-formula HCC additives to help prevent scale build-up and to fight corrosion in your equipment. All are highly concentrated, so a little goes a long way.



HOTSY SOLUTION SELECTOR
What's the best detergent for your next job? Find out with our solution selector. Scan this QR code or visit HOTSY.com

OPTIONS FOR DBA SERIES

- Downstream Detergent Injector

PARTS & ACCESSORIES

Your local Hotsy dealer stocks a number of accessories designed to speed cleaning. The most common accessories are telescoping wands, pivot and non-pivot hose reels, flat surface cleaners and high pressure turbo nozzles.

Hotsy dealers also stock thousands of pressure washer replacement parts such as high pressure hose, trigger guns, high pressure nozzles, pumps, unloaders, filters and wands.



SERVICE & REPAIR

Hotsy has more than 175 local dealers in North America, all factory-trained to properly evaluate your high-pressure cleaning needs.

Hotsy has factory-trained service technicians who will provide on-site maintenance for your cleaning equipment. Our techs have most common replacement parts on their service truck, and will quickly have your washer running smoothly.



FIND OUT MORE ONLINE: HOTSY.COM

Distributed by:

hotsy *Nothing Cleans Like a Hotsy!*

Tel: (800) 525-1976 Fax: (888) 880-9631
www.Hotsy.com email: info@Hotsy.com
P/N 9.801-314.0 Effective 3/16



Specifications & product descriptions subject to change without notice. Hotsy's manufacturing facilities have established and apply a quality and environmental management system to be ISO 9001:2008 and ISO 14001:2001 certified. A member of KÄRCHER North America ©2016 Hotsy

NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We meet the CETA testing specs for machine performance at $\pm 10\%$ and in some cases are tighter within $\pm 5\%$ of listed specifications.